

70041 EPDM STEAM 250 PSI

RUBBER₩©RX[™] 3/4" EPDM STEAM 250 PSI

This heavy duty wire reinforced hose is designed for use in refineries and chemical plants for steam service. The EPDM compound is designed for continual service at 450°F. Drain water from hoses after steam service. Specialized EPDM to resist tube popcorning.

> Black FPDM TUBE:

Wire Braid **REINFORCEMENT:**

> **Black EPDM COVER:**

-40°F to 400°F **TEMPERATURE:**

| PART # | ID (IN) | OD (IN) | WP (PSI) | BEND RADIUS (IN) | WEIGHT | PACKAGING |
|-----------|------------|------------|-------------|------------------------|--------|-----------|
| 70041-075 | 0.75 | 1.18 | 250 | 9 | 0.57 | 50' |
| 70041-100 | 1.00 | 1.45 | 250 | 11 | 0.78 | 50' |
| 70041-125 | 1.25 | 1.71 | 250 | 15 | 1.29 | 50' |
| 70041-150 | 1.50 | 1.95 | 250 | 18 | 2.05 | 50' |
| 70041-200 | 2.00 | 2.52 | 250 | 24 | 3.01 | 50' |

***Not for use with crimped steam ends



! WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.







