

20031 PETROLEUM TRANSFER 300 PSI



This heavy-duty petroleum suction and discharge hose is designed for use with oils, petroleum based products, and refined fuels. For use in offshore oil transfer, tank truck, oilfield transfer and oil pumping applications with aromatic content up to 50%.

TUBE	Black Nitrile
REINFORCEMENT	Spiral Ply Textile
REINFORCEMENT HELIX	Steel Wire
COVER	Black Nitrile
TEMPERATURE	-22F° to 180F°
BRANDING EXAMPLE	RUBBERWORX 4" PETROLEUM TRANSFER 300 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20031-200	2	2.00	51	2 33/64	2.52	64	300	21	11	279	29	1.48	2.20	100
20031-300	3	3.00	76	3 37/64	3.58	91	300	21	14	356	29	2.20	3.27	100
20031-400	4	4.00	102	4 44/64	4.69	119	300	21	18	457	29	3.05	4.54	100
20031-500	5	5.00	127	5 51/64	5.79	147	300	21	29	737	29	5.89	8.77	100
20031-600	6	6.00	152	6 54/64	6.85	174	300	21	38	965	29	7.95	11.83	100