



10191 SINGLE JACKET FIRE HOSE



RUBBERWORX™ SJ FIRE HOSE

This durable single-jacket fire hose is lightweight and designed for use in fire fighting applications.

Natural rubber tube and woven polyester jacket are designed to handle residual chemicals in water transfer applications. UL 19 approved, meets or exceeds NFPA 1961.

TUBE	Black NR
COVER	White Single Polyester Woven Jacket
TEMPERATURE	-40°F to 158°F
BRANDING EXAMPLE	RUBBERWORX SJ FIRE HOSE
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			SERVICE TEST PRESSURE MILL/FIRE HOSE	ACCEPTANCE/ PROOF TEST PRESSURE MILL/FIRE HOSE	BURST TEST PRESSURE MILL/FIRE HOSE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	PSI	PSI	PSI	(lb/ft)	(kg/m)	
10191-150	1 1/2	1.50	38	200	400	600	0.21	0.31	50,100
10191-200	2	2.00	51	200	400	600	0.28	0.42	50,100
10191-250	2 1/2	2.50	64	200	400	600	0.36	0.54	50,100
10191-300	3	3.00	76	200	400	600	0.44	0.65	50,100
10191-400	4	4.00	102	200	400	600	0.63	0.94	50,100

*Service Test Pressure is the annual test pressure and pressure in PSI stenciled on the hose.

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

 888-661-1680

 www.rubberworxhose.com

 sales@rubberworxhose.com