

10191 SINGLE JACKET FIRE HOSE ASSEMBLIES

This durable single-jacket fire hose is lightweight and designed for use in fire fighting applications.

Natural rubber tube and woven polyester jacket are designed to handle residual chemicals in water transfer applications. UL 19 approved, meets or exceeds NFPA 1961.



Tube	Black Synthetic Rubber
Reinforcement	Spiral Textile
Cover	White Single Polyester Woven Jacket
Service Test Pressure	200 PSI
Temperature	-40°F to 158°F

NPSH THREADED MXF ROCKER LUG



Part #	Hose ID (IN)	Assembly OAL (FT)	End 1		End 2		Attachment Method	Approx. Assembly Weight (LBS)
			End Material	Fitting Style	End Material	Fitting Style		
1019-0150-0300-AL-NPSH-RL	1 1/2	25	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	7
1019-0150-0600-AL-NPSH-RL	1 1/2	50	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	12
1019-0150-0900-AL-NPSH-RL	1 1/2	75	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	17
1019-0150-1200-AL-NPSH-RL	1 1/2	100	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	22
1019-0200-0600-AL-NPSH-RL	2	50	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	17
1019-0200-1200-AL-NPSH-RL	2	100	Anodized Aluminum	M-NPSH Rocker Lug	Anodized Aluminum	F-NPSH Rocker Lug	Swage	31

*Service Test Pressure is the annual test pressure and pressure in PSI stenciled on the hose.