

20201 OFFSHORE PETROLEUM TRANSFER 500 PSI



Offshore Petroleum Transfer 500 PSI with Static Grounding Wire is for use on offshore oil rigs to transfer petroleum-based products with up to 50% aromatic content. This hose has a high working pressure of 500 PSI.

TUBE	Black Nitrile
REINFORCEMENT	Spiral-Plied Textile With Dual Steel Wire Helix
COVER	Black Neoprene
TEMPERATURE	-35°F to 200°F
BRANDING EXAMPLE	RUBBERWORX OFFSHORE PETRO TRANSFER 500 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20201-300	3	3.00	76	4 1/64	4.01	102	500	34	10	254	29	3.61	5.37	100
20201-400	4	4.00	102	5 6/64	5.09	129	500	34	12	305	29	5.02	7.47	100