


SCHEDULE 40

FITTING CONNECTION TYPE:

Stub End Type C

PIPE SCHEDULE:

40

MATERIALS
STANDARDS:

ASTM A403; ASTM A960;

ASTM B16.9; MSS SP-43

Part Number	Material	NPS (in)	Outside Diameter (in) W	Flange Diameter (in) D	Length (in) L	Radius (in) R	Inside Diameter (in) ID	Wall Thickness (in) T	Weight Each (lb)
RBX-STUBC-SCD40-100-304	304 Stainless Steel	1"	1.315	2.000	2.000	0.120	1.049	0.133	0.200
RBX-STUBC-SCD40-100-316	316 Stainless Steel	1"	1.315	2.000	2.000	0.120	1.049	0.133	0.200
RBX-STUBC-SCD40-100-CS	Carbon Steel	1"	1.315	2.000	2.000	0.120	1.049	0.133	0.200
RBX-STUBC-SCD40-125-304	304 Stainless Steel	1-1/4"	1.660	2.500	2.000	0.190	1.375	0.140	0.300
RBX-STUBC-SCD40-125-316	316 Stainless Steel	1-1/4"	1.660	2.500	2.000	0.190	1.375	0.140	0.300
RBX-STUBC-SCD40-125-CS	Carbon Steel	1-1/4"	1.660	2.500	2.000	0.190	1.375	0.140	0.300
RBX-STUBC-SCD40-150-304	304 Stainless Steel	1-1/2"	1.900	2.875	2.000	0.250	1.610	0.145	0.380
RBX-STUBC-SCD40-150-316	316 Stainless Steel	1-1/2"	1.900	2.875	2.000	0.250	1.610	0.145	0.380
RBX-STUBC-SCD40-150-CS	Carbon Steel	1-1/2"	1.900	2.875	2.000	0.250	1.610	0.145	0.380
RBX-STUBC-SCD40-200-304	304 Stainless Steel	2"	2.375	3.625	2.500	0.310	2.067	0.154	0.550
RBX-STUBC-SCD40-200-316	316 Stainless Steel	2"	2.375	3.625	2.500	0.310	2.067	0.154	0.550
RBX-STUBC-SCD40-200-CS	Carbon Steel	2"	2.375	3.625	2.500	0.310	2.067	0.154	0.550
RBX-STUBC-SCD40-250-304	304 Stainless Steel	2-1/2"	2.875	4.125	2.500	0.310	2.469	0.203	0.800
RBX-STUBC-SCD40-250-316	316 Stainless Steel	2-1/2"	2.875	4.125	2.500	0.310	2.469	0.203	0.800
RBX-STUBC-SCD40-250-CS	Carbon Steel	2-1/2"	2.875	4.125	2.500	0.310	2.469	0.203	0.800
RBX-STUBC-SCD40-300-304	304 Stainless Steel	3"	3.500	5.000	2.500	0.380	3.068	0.216	1.100
RBX-STUBC-SCD40-300-316	316 Stainless Steel	3"	3.500	5.000	2.500	0.380	3.068	0.216	1.100
RBX-STUBC-SCD40-300-CS	Carbon Steel	3"	3.500	5.000	2.500	0.380	3.068	0.216	1.100
RBX-STUBC-SCD40-400-304	304 Stainless Steel	4"	4.500	6.188	3.000	0.440	4.026	0.237	1.800
RBX-STUBC-SCD40-400-316	316 Stainless Steel	4"	4.500	6.188	3.000	0.440	4.026	0.237	1.800
RBX-STUBC-SCD40-400-CS	Carbon Steel	4"	4.500	6.188	3.000	0.440	4.026	0.237	1.800
RBX-STUBC-SCD40-600-304	304 Stainless Steel	6"	6.625	8.500	3.500	0.500	6.065	0.280	3.700
RBX-STUBC-SCD40-600-316	316 Stainless Steel	6"	6.625	8.500	3.500	0.500	6.065	0.280	3.700
RBX-STUBC-SCD40-600-CS	Carbon Steel	6"	6.625	8.500	3.500	0.500	6.065	0.280	3.700
RBX-STUBC-SCD40-800-304	304 Stainless Steel	8"	8.625	10.625	4.000	0.500	7.981	0.322	5.900
RBX-STUBC-SCD40-800-316	316 Stainless Steel	8"	8.625	10.625	4.000	0.500	7.981	0.322	5.900
RBX-STUBC-SCD40-800-CS	Carbon Steel	8"	8.625	10.625	4.000	0.500	7.981	0.322	5.900
RBX-STUBC-SCD40-1000-304	304 Stainless Steel	10"	10.750	12.750	5.000	0.500	10.020	0.365	10.500
RBX-STUBC-SCD40-1000-316	316 Stainless Steel	10"	10.750	12.750	5.000	0.500	10.020	0.365	10.500
RBX-STUBC-SCD40-1000-CS	Carbon Steel	10"	10.750	12.750	5.000	0.500	10.020	0.365	10.500
RBX-STUBC-SCD40-1200-304	304 Stainless Steel	12"	12.750	15.000	6.000	0.500	11.938	0.375	15.000
RBX-STUBC-SCD40-1200-316	316 Stainless Steel	12"	12.750	15.000	6.000	0.500	11.938	0.375	15.000
RBX-STUBC-SCD40-1200-CS	Carbon Steel	12"	12.750	15.000	6.000	0.500	11.938	0.375	15.000