


SCHEDULE 10

FITTING CONNECTION TYPE:

Stub End Type C

PIPE SCHEDULE:

10

MATERIALS
STANDARDS:

ASTM A403; ASTM A960;
ASTM B16.9; MSS SP-43

Part Number	Material	NPS (in)	Outside Diameter (in) W	Flange Diameter (in) D	Length (in) L	Radius (in) R	Inside Diameter (in) ID	Wall Thickness (in) T	Weight Each (lb)
RBX-STUBC-SCD10-100-304	304 Stainless Steel	1	1.035	2.000	2.000	1/32	1.097	0.109	0.150
RBX-STUBC-SCD10-100-316	316 Stainless Steel	1	1.035	2.000	2.000	1/32	1.097	0.109	0.150
RBX-STUBC-SCD10-100-CS	Carbon Steel	1	1.035	2.000	2.000	1/32	1.097	0.109	0.150
RBX-STUBC-SCD10-125-304	304 Stainless Steel	1 1/4	1.688	2.500	2.000	1/32	1.552	0.109	0.200
RBX-STUBC-SCD10-125-316	316 Stainless Steel	1 1/4	1.688	2.500	2.000	1/32	1.552	0.109	0.200
RBX-STUBC-SCD10-125-CS	Carbon Steel	1 1/4	1.688	2.500	2.000	1/32	1.552	0.109	0.200
RBX-STUBC-SCD10-150-304	304 Stainless Steel	1 1/2	2.875	2.875	2.000	1/32	1.683	0.109	0.250
RBX-STUBC-SCD10-150-316	316 Stainless Steel	1 1/2	2.875	2.875	2.000	1/32	1.683	0.109	0.250
RBX-STUBC-SCD10-150-CS	Carbon Steel	1 1/2	2.875	2.875	2.000	1/32	1.683	0.109	0.250
RBX-STUBC-SCD10-200-304	304 Stainless Steel	2	2.375	3.625	2.500	1/32	2.156	0.109	0.400
RBX-STUBC-SCD10-200-316	316 Stainless Steel	2	2.375	3.625	2.500	1/32	2.156	0.109	0.400
RBX-STUBC-SCD10-200-CS	Carbon Steel	2	2.375	3.625	2.500	1/32	2.156	0.109	0.400
RBX-STUBC-SCD10-250-304	304 Stainless Steel	2 1/2	2.688	4.125	2.500	1/32	2.634	0.122	0.500
RBX-STUBC-SCD10-250-316	316 Stainless Steel	2 1/2	2.688	4.125	2.500	1/32	2.634	0.122	0.500
RBX-STUBC-SCD10-250-CS	Carbon Steel	2 1/2	2.688	4.125	2.500	1/32	2.634	0.122	0.500
RBX-STUBC-SCD10-300-304	304 Stainless Steel	3	3.500	5.000	2.500	1/32	3.260	0.122	0.600
RBX-STUBC-SCD10-300-316	316 Stainless Steel	3	3.500	5.000	2.500	1/32	3.260	0.122	0.600
RBX-STUBC-SCD10-300-CS	Carbon Steel	3	3.500	5.000	2.500	1/32	3.260	0.122	0.600
RBX-STUBC-SCD10-400-304	304 Stainless Steel	4	4.500	6.188	3.000	1/32	4.260	0.122	1.000
RBX-STUBC-SCD10-400-316	316 Stainless Steel	4	4.500	6.188	3.000	1/32	4.260	0.122	1.000
RBX-STUBC-SCD10-400-CS	Carbon Steel	4	4.500	6.188	3.000	1/32	4.260	0.122	1.000
RBX-STUBC-SCD10-600-304	304 Stainless Steel	6	6.625	8.500	3.500	1/16	6.357	0.134	1.950
RBX-STUBC-SCD10-600-316	316 Stainless Steel	6	6.625	8.500	3.500	1/16	6.357	0.134	1.950
RBX-STUBC-SCD10-600-CS	Carbon Steel	6	6.625	8.500	3.500	1/16	6.357	0.134	1.950
RBX-STUBC-SCD10-800-304	304 Stainless Steel	8	8.625	10.625	4.000	1/16	8.329	0.148	3.100
RBX-STUBC-SCD10-800-316	316 Stainless Steel	8	8.625	10.625	4.000	1/16	8.329	0.148	3.100
RBX-STUBC-SCD10-800-CS	Carbon Steel	8	8.625	10.625	4.000	1/16	8.329	0.148	3.100
RBX-STUBC-SCD10-1000-304	304 Stainless Steel	10	10.750	12.750	5.000	1/16	10.422	0.165	4.900
RBX-STUBC-SCD10-1000-316	316 Stainless Steel	10	10.750	12.750	5.000	1/16	10.422	0.165	4.900
RBX-STUBC-SCD10-1000-CS	Carbon Steel	10	10.750	12.750	5.000	1/16	10.422	0.165	4.900
RBX-STUBC-SCD10-1200-304	304 Stainless Steel	12	12.750	15.000	6.000	1/16	12.392	0.180	7.100
RBX-STUBC-SCD10-1200-316	316 Stainless Steel	12	12.750	15.000	6.000	1/16	12.392	0.180	7.100
RBX-STUBC-SCD10-1200-CS	Carbon Steel	12	12.750	15.000	6.000	1/16	12.392	0.180	7.100