

## 40172 HD SBR MATERIAL SUCTION



|                                 |                                                       |
|---------------------------------|-------------------------------------------------------|
| <b>TUBE</b>                     | Black SBR                                             |
| <b>REINFORCEMENT</b>            | Spiral Textile with a PVC Helix                       |
| <b>COVER</b>                    | Black PVC/Nitrile                                     |
| <b>TEMPERATURE</b>              | -40°F to 140°F                                        |
| <b>BRANDING EXAMPLE</b>         | RUBBERWORX HD SBR MATERIAL<br>SUCTION                 |
| <b>PACKAGING SPECIFICATIONS</b> | Roll Or Cut Length Wrapped In<br>Plastic For Shipping |

| PART #    | ID            |              |             | OD            |              |             | WP  |     | BEND RADIUS  |             | VACUUM PRESSURE | WEIGHT  |        | PACKAGING (ft) |
|-----------|---------------|--------------|-------------|---------------|--------------|-------------|-----|-----|--------------|-------------|-----------------|---------|--------|----------------|
|           | Fraction (in) | Decimal (in) | Metric (mm) | Fraction (in) | Decimal (in) | Metric (mm) | PSI | Bar | Decimal (in) | Metric (mm) | inHg            | (lb/ft) | (kg/m) |                |
| 40172-150 | 1 1/2         | 1.50         | 38          | 1 58/64       | 1.90         | 48          | 45  | 3   | 2            | 51          | 30              | 0.37    | 0.55   | 100            |
| 40172-200 | 2             | 2.00         | 51          | 2 26/64       | 2.40         | 61          | 40  | 3   | 3            | 64          | 30              | 0.50    | 0.74   | 100            |
| 40172-250 | 2 1/2         | 2.50         | 64          | 3             | 3.00         | 76          | 35  | 2   | 3            | 64          | 30              | 0.88    | 1.31   | 100            |
| 40172-300 | 3             | 3.00         | 76          | 3 32/64       | 3.50         | 89          | 35  | 2   | 3            | 76          | 30              | 1.10    | 1.64   | 100            |
| 40172-400 | 4             | 4.00         | 102         | 4 40/64       | 4.63         | 118         | 30  | 2   | 5            | 114         | 30              | 1.77    | 2.63   | 100            |
| 40172-500 | 5             | 5.00         | 127         | 5 49/64       | 5.76         | 146         | 30  | 2   | 5            | 127         | 28              | 2.47    | 3.68   | 100            |
| 40172-600 | 6             | 6.00         | 152         | 6 51/64       | 6.80         | 173         | 30  | 2   | 9            | 234         | 28              | 3.08    | 4.58   | 100            |
| 40172-800 | 8             | 8.00         | 203         | 9 3/64        | 9.04         | 230         | 30  | 2   | 15           | 381         | 27              | 5.65    | 8.41   | 20             |