

Quality Ducting Products & Accessories You Can Trust



Your Trusted Partner For In-Stock HVAC Solutions



A SINGER INDUSTRIAL COMPANY

Our team specializes in HVAC products, covering everything from heating and cooling to air transfer, couplings, and adapters. With a strong understanding of your industry, Shipyard Supply stocks the ducting, hose, and adapters you need to keep your projects running smoothly.

ALABAMA

5495 East Rite Road
Theodore, AL 36582
P. (251) 653-4334

LOUISIANA

2828 Lausat Street
Metairie, LA 70001
P. (504) 833-8345

FLORIDA

1755 Olive Street
Lakeland, FL 33815
P. (863) 777-8990

TEXAS

930 E. Sam Houston Pkwy
South Pasadena, TX 77503
P. (346) 701-8881

SHIPYARD SUPPLY DUCTING SOLUTIONS



Yellow & Black Supply Duct

- PVC polyester tube with carbon steel helix reinforcement and a yellow & black polyester cover, designed for durability in demanding applications
- Operates within a temperature range of -20°F to 180°F, available in 8"–24" IDs with a 6" pitch and 25 ft lengths



White Supply Duct

- PVC polyester tube with carbon steel helix reinforcement and a white PVC polyester cover for strength and flexibility
- Operates within a temperature range of -20°F to 180°F, available in 8"–24" IDs with a 6" pitch and 25 ft lengths




White Insulated Duct

- PVC polyester tube with carbon steel helix reinforcement and a yellow & black PVC polyester cover, built for strength and flexibility in standard applications
- Operates within a temperature range of -20°F to 180°F, available in 8"–24" IDs with a 6" pitch and 25 ft lengths



Black Heater Duct

- Polyurethane tube with carbon steel helix reinforcement and a black PVC polyester cover, offering durability across extreme temperatures from -60°F to 400°F
- Available in 8"–24" IDs with a 3" pitch and 25 ft lengths



Orange/White & Green/White Return Ducts

- Polyurethane tube with carbon steel helix reinforcement and a PVC polyester cover, providing durability and flexibility for a range of applications
- Operates within a temperature range of -20°F to 180°F and is available in 8"–24" IDs with a 3" pitch and standard 25 ft lengths



Ceiling Tile Kit

- Available in a 12" ID configuration with durable construction suited for standard ducting applications
- Offered in 8 ft and 12 ft lengths to accommodate a variety of installation requirements



Blower Tubing

- Heavy duty clear blower tubing designed for durability and efficient airflow in demanding applications
- Available in 12"–32" IDs, with lengths that vary by diameter to meet different system requirements



Duct Adapters

- Wyes and straight reducers designed for efficient airflow distribution and system transitions
- Available in 8"–24" IDs, offered in both standard and reducing configurations to fit various applications