

10211 SINGLE JACKET MILL HOSE



This durable single jacket mill hose is lightweight and designed for use in construction, dewatering, agricultural and industrial applications.

Natural rubber tube and woven polyester jacket are designed to handle residual chemicals in water transfer applications.

TUBE	Black NR
COVER	White Single Polyester Woven Jacket
TEMPERATURE	-40°F to 158°F
BRANDING EXAMPLE	RUBBERWORX SJ MILL HOSE
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping
SPECIAL NOTE	Not For Use In Fire Fighting Applications

PART #	ID			SERVICE TEST PRESSURE MILL/FIRE HOSE	ACCEPTANCE/ PROOF TEST PRESSURE MILL/FIRE HOSE	BURST TEST PRESSURE MILL/FIRE HOSE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	PSI	PSI	PSI	(lb/ft)	(kg/m)	
10211-150	1 1/2	1.50	38	150	300	450	0.20	0.30	50, 100
10211-200	2	2.00	51	150	300	450	0.27	0.40	50, 100
10211-300	3	2.50	64	150	300	450	0.43	0.64	50, 100
10211-400	4	3.00	76	150	300	450	0.62	0.92	50, 100
10211-600	6	4.00	102	150	300	450	1.00	1.49	50, 100

*Service Test Pressure is the annual test pressure and pressure in PSI stenciled on the hose.

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.