



50031 WIRE AIR BRAID HIGH TEMP 600 PSI



This heavy duty high temp wire reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications.

Specially formulated CPE tube and cover provide the highest temperature ratings for hot compressed air. The ozone and abrasion resistant cover holds up to the toughest applications.

TUBE	Black CPE
REINFORCEMENT	Wire Braid
COVER	Yellow CPE Blend
TEMPERATURE	-40°F to 300°F
BRANDING EXAMPLE	RUBBERWORK 600 PSI HT WIRE BRAID AIR
PACKAGING SPECIFICATIONS	Roll or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
50031-075	3/4	0.75	19	1 27/64	1.42	36	600	41	0.60	0.89	100
50031-100	1	1.00	25	1 60/64	1.93	36	600	41	0.80	1.19	100
50031-150	1 1/2	1.50	38	2	2.00	51	600	41	1.03	1.53	100
50031-200	2	2.00	51	2 36/64	2.57	65	600	41	1.38	2.05	100
50031-300	3	3.00	76	3 54/64	3.84	98	600	41	1.38	2.05	100
50031-400	4	4.00	102	4 51/64	4.79	122	600	41	4.11	6.12	100

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

 888-661-1680

 www.rubberworxhose.com

 sales@rubberworxhose.com