

50051 TEXTILE AIR BRAID 300 PSI



This heavy duty textile reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications.

The ozone and abrasion resistant cover holds up to the toughest applications.

TUBE	Black NR/SBR Blend
REINFORCEMENT	Braided Textile
COVER	Wrapped Yellow SBR/EPDM Blend
TEMPERATURE	-22°F to 180°F
BRANDING EXAMPLE	RUBBERWORK 300 PSI TEXTILE BRAID AIR
PACKAGING SPECIFICATIONS	Roll or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
50051-050	1/2	0.50	13	56/64	0.87	22	300	21	0.22	0.33	100
50051-063	5/8	0.63	16	63/64	0.98	25	300	21	0.30	0.45	100
50051-075	3/4	0.75	19	1 9/64	1.14	29	300	21	0.38	0.57	100
50051-100	1	1.00	25	1 27/64	1.42	36	300	21	0.50	0.74	100
50051-125	1 1/4	1.25	32	1 47/64	1.73	44	300	21	0.61	0.91	100
50051-150	1 1/2	1.50	38	2 1/64	2.01	51	300	21	0.71	1.06	100
50051-200	2	2.00	51	2 36/64	2.56	65	300	21	1.38	2.05	100
50051-250	2 1/2	2.50	64	3 10/64	3.15	80	300	21	1.56	2.32	100
50051-300	3	3.00	76	3 40/64	3.62	92	300	21	1.95	2.90	100
50051-400	4	4.00	102	4 42/64	4.65	118	300	21	2.53	3.76	100

! WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.