

10021 PVC WATER SUCTION AND DISCHARGE



This light-duty water suction and discharge hose is designed for use in construction, dewatering, agriculture, and various industrial applications.

With a durable PVC tube, it effectively handles water with residual chemicals, making it ideal for transferring chemically-treated fluids. Built for reliable performance, it ensures functionality and safety across a range of tasks.

TUBE	Clear PVC
REINFORCEMENT HELIX	White PVC
COVER	Clear PVC
TEMPERATURE	-23°F to 140°F
BRANDING EXAMPLE	RUBBERWORX PVC WATER SUCTION & DISCHARGE 100 PSI
PACKAGING SPECIFICATIONS	Roll or cut length wrapped in plastic for shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
10021-075	3/4	0.75	19	1 1/64	1.02	26	100	7	2	51	28	0.21	0.31	100
10021-100	1	1.00	25	1 19/64	1.29	33	100	7	3	76	28	0.29	0.43	100
10021-125	1 1/4	1.25	32	1 36/64	1.56	40	90	6	4	102	28	0.38	0.57	100
10021-150	1 1/2	1.50	38	1 54/64	1.84	47	90	6	4	102	28	0.49	0.73	100
10021-200	2	2.00	51	2 25/64	2.39	61	70	5	5	127	28	0.72	1.07	100
10021-250	2 1/2	2.50	64	2 59/64	2.92	74	65	4	7	178	28	0.99	1.47	100
10021-300	3	3.00	76	3 29/64	3.46	88	55	4	8	203	28	1.29	1.92	20, 60
10021-400	4	4.00	102	4 36/64	4.56	116	50	3	12	305	28	2.05	3.05	20, 100
10021-500	5	5.00	127	5 42/64	5.65	144	45	3	20	508	28	3.01	4.48	100
10021-600	6	6.00	152	6 51/64	6.80	173	45	3	23	584	28	4.45	6.62	20, 100
10021-800	8	8.00	203	8 61/64	8.95	227	40	3	34	864	28	6.86	10.21	20, 60
10021-1000	10	10.00	254	11 22/64	11.34	288	40	3	40	1016	28	12.05	17.93	20, 60
10021-1200	12	12.00	305	13 12/64	13.19	335	35	2	50	1270	28	15.27	22.72	20, 60

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



888-661-1680



www.rubberworxhose.com



sales@rubberworxhose.com