

10131 RUGGED CHILLER DISCHARGE 150 PSI



This heavy-duty water discharge hose is specifically designed for chiller applications, featuring a durable synthetic rubber blend uniquely formulated to handle glycol solutions.

It outperforms standard SBR in conventional rubber water discharge hoses, making it an ideal choice for demanding environments that require reliable, repeated use.

TUBE	Black Synthetic Blend
REINFORCEMENT	Spiral 4-Ply Textile
COVER	Black Synthetic Blend
TEMPERATURE	-25°F to 180°F
BRANDING EXAMPLE	4" RUGGED CHILLER DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS	Roll or Cut Length wrapped in plastic for shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
10131-150	1 1/2	1.50	38	2	1.77	45	150	10	1.19	0.80	100
10131-200	2	2.00	51	2 32/64	2.28	58	150	10	1.40	0.94	100
10131-250	2 1/2	2.50	64	3 4/64	2.76	70	150	10	1.79	1.20	100
10131-300	3	3.00	76	3 35/64	3.27	83	150	10	2.23	1.50	100
10131-400	4	4.00	102	4 37/64	4.29	109	150	10	3.27	2.20	100
10131-500	5	5.00	127	5 36/64	5.39	137	150	10	5.65	3.80	100
10131-600	6	6.00	152	6 34/64	6.38	162	150	10	6.70	4.50	100
10131-800	8	8.00	203	8 36/64	8.54	217	150	10	9.08	6.10	100