

20011 PETROLEUM SUCTION AND DISCHARGE 150



TUBE	Black Nitrile
REINFORCEMENT	Spiral Ply Textile With Wire Helix
COVER	Black Nitrile
TEMPERATURE	-22°F to 180°F
BRANDING EXAMPLE	RUBBERWORX 4" PETROLEUM SUCTION AND DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20011-075	3/4	0.75	19	1 12/64	1.18	30	150	10	4	102	29	0.40	0.60	100
20011-100	1	1.00	25	1 27/64	1.42	36	150	10	4	102	29	0.48	0.71	100
20011-125	1 1/4	1.25	32	1 44/64	1.69	43	150	10	5	127	29	0.61	0.91	100
20011-150	1 1/2	1.50	38	1 60/64	1.93	49	150	10	7	178	29	0.79	1.18	100
20011-200	2	2.00	51	2 28/64	2.44	62	150	10	10	254	29	1.11	1.65	100
20011-250	2 1/2	2.50	64	2 61/64	2.95	75	150	10	12	305	29	1.43	2.13	100
20011-300	3	3.00	76	3 35/64	3.54	90	150	10	15	381	29	1.89	2.81	100
20011-300	3	3.00	76	3 35/64	3.54	90	150	10	15	381	29	1.89	2.81	100
20011-400	4	4.00	102	4 39/64	4.61	117	150	10	18	457	29	2.73	4.06	100
20011-600	6	6.00	152	6 44/64	6.69	170	150	10	30	762	27	5.29	7.87	100
20011-800	8	8.00	203	8 58/64	8.90	226	150	10	30	762	27	9.69	14.42	20, 60
20011-1000	10	10.00	254	11 6/64	11.10	282	150	10	42	1067	24	11.60	17.26	20, 60
20011-1200	12	12.00	305	13 20/64	13.31	338	150	10	60	1524	24	14.50	21.58	20, 60