

20022 PETROLEUM TRANSFER 150 PSI



This heavy-duty petroleum suction and discharge hose is designed for use with oils, petroleum based products, and refined fuels. For use in offshore oil transfer, tank truck, oilfield transfer and oil pumping applications with aromatic content up to 50%.

TUBE	Black Nitrile
REINFORCEMENT	Spiral Ply Textile With Wire Helix
COVER	Black Nitrile - CORRUGATED
TEMPERATURE	-22°F to 180°F
BRANDING EXAMPLE	RUBBERWORX™ PETROLEUM TRANSFER 150 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20022-200	2	2.00	51	2 32/64	2.50	64	150	10	10	254	29	1.11	1.65	100
20022-250	2 1/2	2.50	64	3	3.00	76	150	10	12	305	29	1.43	2.13	100
20022-300	3	3.00	76	3 32/64	3.50	89	150	10	15	381	29	1.89	2.81	100
20022-400	4	4.00	102	4 38/64	4.60	117	150	10	18	457	29	2.73	4.06	100
20022-600	6	6.00	152	6 38/64	6.60	168	150	10	30	762	29	5.29	7.87	100