

20042 RED PETROLEUM TRANSFER 150 PSI



This heavy-duty petroleum suction and discharge hose is designed for use with oils, petroleum based products, and refined fuels. For use in offshore oil transfer, tank truck, oilfield transfer and oil pumping applications with aromatic content up to 50%. Corrugated cover design for improved flexibility.

TUBE	Black Nitrile
REINFORCEMENT	Spiral Ply Textile With Wire Helix
COVER	Red Nitrile
TEMPERATURE	-22F° to 180F°
BRANDING EXAMPLE	RUBBERWORX™ PETROLEUM TRANSFER 150 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20042-200	2	2.00	51	2 32/64	2.50	64	150	10	10	254	29	1.11	1.65	100
20042-250	2 1/2	2.50	64	3	3.00	76	150	10	12	305	29	1.43	2.13	100
20042-300	3	3.00	76	3 32/64	3.50	89	150	10	15	381	29	1.89	2.81	100
20042-400	4	4.00	102	4 38/64	4.60	117	150	10	18	457	29	2.73	4.06	100
20042-600	6	6.00	152	6 45/64	6.70	170	150	10	24	610	20	3.33	4.96	100