


## 20162 XFLEX PETROLEUM TRANSFER 250 PSI



XFLEX 250 PSI Petroleum Transfer Hose - Rubberworx's highly flexible, heavy-duty rubber suction and discharge hose with a dual steel wire helix. This versatile petroleum transfer hose is more flexible and lighter than traditional tank truck hoses in its class, making it easier to lift, carry, and maneuver. It is also designed with a higher working pressure, allowing it to cover a broader range of applications. Suitable for use with petroleum-based products containing up to 50% aromatic content.

<b>TUBE</b>	Black Nitrile
<b>REINFORCEMENT</b>	Spiral-Plied Textile With Dual Steel Wire Helix
<b>COVER</b>	Black Nitrile
<b>TEMPERATURE</b>	-40°F to 200°F
<b>BRANDING EXAMPLE</b>	RUBBERWORX XFLEX PETROLEUM TRANSFER 250 PSI
<b>PACKAGING SPECIFICATIONS</b>	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
20162-075	3/4	0.75	19	1 13/64	1.20	30	250	17	1	19	29	0.44	0.65	100
20162-100	1	1.00	25	1 29/64	1.45	37	250	17	1	25	29	0.55	0.82	100
20162-150	1 1/2	1.50	38	1 58/64	1.91	49	250	17	2	38	29	0.73	1.09	100
20162-200	2	2.00	51	2 28/64	2.43	62	250	17	2	51	29	0.96	1.43	100
20162-250	2 1/2	2.50	64	3	3.00	76	250	17	3	64	29	1.41	2.10	100
20162-300	3	3.00	76	3 32/64	3.50	89	250	17	3	76	29	1.69	2.51	100
20162-400	4	4.00	102	4 36/64	4.56	116	250	17	4	102	29	2.42	3.60	100
20162-600	6	6.00	152	6 40/64	6.62	168	250	17	6	152	29	4.43	6.59	100

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).