


30051 LPG DELIVERY 350 PSI



For residential and commercial delivery/transfer of liquid propane gas. Excellent cold weather flexibility. The hose meets UL, CGA and DOT requirements. Hoses are approved for use in LPG bobtail delivery, LPG dispensing, and LPG industrial portable heater applications only.

TUBE	Black Nitrile
REINFORCEMENT	Spiral Textile
COVER	Black SBR
TEMPERATURE	-40°F to 180°F
BRANDING EXAMPLE	RUBBERWORX LPG DELIVERY 350 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
30051-038	3/8	0.38	10	45/64	0.70	18	350	24	3	76	10	0.78	1.16	100
30051-050	1/2	0.50	13	60/64	0.93	24	351	24	5	127	10	1.10	1.64	100
30051-075	3/4	0.75	19	1 15/64	1.23	31	352	24	6	152	10	1.21	1.80	100
30051-100	1	1.00	25	1 31/64	1.49	38	353	24	8	203	10	1.57	2.34	100
30051-125	1 1/4	1.25	32	1 51/64	1.80	46	354	24	10	254	10	2.40	3.57	100
30051-150	1 1/2	1.50	38	2 3/64	2.04	52	355	24	12	305	10	3.20	4.76	100
30051-200	2	2.00	51	2 55/64	2.86	73	356	25	14	356	10	7.20	10.71	100

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



888-661-1680



www.rubberworxhose.com



sales@rubberworxhose.com