


80062 GREEN CORRUGATED WHITE TUBE UHMW CHEMICAL SUCTION 250 PSI



TUBE	White UHMW-PE
REINFORCEMENT	Spiral Ply Textile with Dual Steel Wire Helix
COVER	Green EPDM
TEMPERATURE	-22°F to 250°F
BRANDING EXAMPLE	UHMW CHEMICAL SUCTION AND DISCHARGE 250 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
80062-075	3/4	0.75	19	1 14/64	1.22	31	250	17	4	102	29	0.43	0.64	100
80062-100	1	1.00	25	1 29/64	1.46	37	250	17	5	127	29	0.56	0.83	100
80062-125	1 1/4	1.25	32	1 47/64	1.73	44	250	17	8	203	29	0.90	1.34	100
80062-150	1 1/2	1.50	38	1 62/64	1.97	50	250	17	8	203	29	0.90	1.34	100
80062-200	2	2.00	51	2 31/64	2.48	63	250	17	12	305	29	1.01	1.50	100
80062-250	3	3.00	76	3 4/64	3.07	78	250	17	18	457	29	1.23	1.83	100
80062-300	3	3.00	76	3 45/64	3.70	94	250	17	22	559	29	1.41	2.10	100
80062-400	4	4.00	102	4 46/64	4.72	120	250	17	26	660	29	1.90	2.83	100