

80202 BLACK CORRUGATED WHITE TUBE UHMW CHEMICAL SUCTION 250 PSI



TUBE	White UHMW-PE
REINFORCEMENT	Spiral Ply Textile with Dual Steel Wire Helix
COVER	Black EPDM
TEMPERATURE	-22°F to 250°F
BRANDING EXAMPLE	UHMW CHEMICAL SUCTION AND DISCHARGE 250 PSI
PACKAGING SPECIFICATIONS	Roll Or Cut Length Wrapped In Plastic For Shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
80202-075	3/4	0.75	19	1 13/64	1.20	30	250	17	4	89	29	0.55	0.82	100
80202-100	1	1.00	25	1 32/64	1.50	38	250	17	4	102	29	0.65	0.97	100
80202-125	1 1/4	1.25	32	1 48/64	1.75	44	250	17	5	127	29	0.80	1.19	100
80202-150	1 1/2	1.50	38	2 4/64	2.06	51	250	17	6	152	29	1.00	1.49	100
80202-250	2	2.00	51	2 38/64	2.60	67	250	17	8	203	29	1.35	2.01	100
80202-300	3	3.00	76	3 4/64	3.06	79	250	17	11	279	29	1.80	2.68	100
80202-300	3	3.00	76	3 42/64	3.65	92	250	17	17	432	29	2.15	3.20	100
80202-400	4	4.00	102	4 45/64	4.70	118	250	17	24	610	29	2.85	4.24	100