

## TYPE D XLOCK FITTING

### FEMALE COUPLER X FEMALE NPT THREAD

**MATERIAL:** Aluminum, 316 Stainless Steel  
**GASKET:** Nitrile  
**CAM ARM:** 304 Stainless Steel  
**BRANDING:** Rubberworx

ALUMINUM



316 STAINLESS STEEL



Type D fittings are frequently threaded onto pipes, threaded hose ends, or manifold assemblies, and are subject to regular connection and disconnection. XLOCK fittings are exclusively engineered for use with liquids

Size	Aluminum Part #	316 Stainless Steel Part #	Max. Width With Cam Arms Closed	Overall Length (L)	Exposed Length (E)	Minimum ID (I)	Max. Width With Cam Arms Extended
1.50"	RBX-D-AL-150-XL	RBX-D-316-150-XL	3.83"	2.843"	2.370"	1.560"	7.967"
2.00"	RBX-D-AL-200-XL	RBX-D-316-200-XL	4.21"	3.156"	2.531"	1.937"	8.340"
3.00"	RBX-D-AL-300-XL	RBX-D-316-300-XL	5.68"	3.718"	2.849"	2.937"	10.435"
4.00"	RBX-D-AL-400-XL	RBX-D-316-400-XL	6.78"	4.030"	2.994"	3.750"	11.538"
6.00"	RBX-D-AL-600-XL	RBX-D-316-600-XL	9.34"	4.531"	2.814"	5.750"	16.060"